

Revision: 26.05.2023

Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name:

BIOFARBA 008

Polysilicone paint

Relevant identified uses of the substance or mixture and uses advised against

Life cycle stages

C/PW Consumer use / Widespread use by professional workers

Sector of Use

SU19 Building and construction work

Product category

PC9a Coatings and paints, thinners, paint removers

Process category

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC19 Manual activities involving hand contact

Environmental release category

ERC10a / ERC11a Widespread use of articles with low release

Article category

AC0 Other

Application of the substance / the preparation

Dispersion paint/ Latex paint - Product for an industrial, technical and private use for coating building surfaces. For all other uses is advised against/ not recommended.

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

KREISEL - Technika Budowlana Sp. z o.o. ul. Szarych Szeregów 23 60-462 Poznań Poland

Tel. +48 61 846 79 00 Fax +48 61 846 79 09 sekretariat@kreisel.pl www.kreisel.pl

Further information obtainable from:

Bartosz Polaczyk - Tel.: +48 510 022 908, +48 61 84 67 966, bartosz.polaczyk@kreisel.pl On working days 8 a.m. - 4 p.m.

Emergency telephone number



National poisons information centre: +44/(0)171 - 635 9191

National Health Service: 111 European emergency call: 112



Revision: 26.05.2023

Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8)

BIOFARBA 008

(Contd. of page 1)

SECTION 2: Hazards identification

Classification of the substance or mixture

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Label elements

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms

Void

Signal word

Void

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container in keeping with local and national regulations.

Additional information:

EUH208 Contains 2-Octyl-2H-isothiazol-3-one, 4,5-dichloro-2-octyl-2H-isothiazol-3-one, 2-Methyl-2H-isothiazol-3-one, 1,2-Benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Other hazards

No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

Chemical characterization: Substances

This product is a mixture.

Mixtures

Description:

Mixture of acrylat dispersion and fillers with nonhazardous additions.

Dangerous components:		
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 REACH: 01-2119489379-17	Titanium dioxide (<1% particles ≤ 10μm, Note 10)	5 - 10%
CAS: 12001-26-2 EC number: 601-648-2 REACH: ¹	Mica - Potassium aluminum silicate (Muscovite)	1 - 2.5%

(Contd. on page 3)



Revision: 26.05.2023

Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8)

BIOFARBA 008

CAS: 57-55-6 EINECS: 200-338-0	Propane-1,2-diol	(Contd. of page 2) 1 - 2.5%
REACH: 01-2119456809-23 CAS: 2634-33-5	1,2-Benzisothiazol-3(2H)-one	< 0.01%
EINECS: 220-120-9 Index number: 613-088-00- REACH: 01-2120761540-60	H315; Škin Sens. 1, H317 Specific concentration limit: Skin Sens. 1;H317: C ≥ 0.05 %	
CAS: 886-50-0 EINECS: 212-950-5 REACH: ²	2-tert-Butylamino-4-ethylamino-6-methylthio-s-triazine (Terbutryn) ♣ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ♠ Acute Tox. 4, H302; Skin Sens. 1B, H317 Specific concentration limit: Skin Sens.1B; H317: C ≥ 3 %	≥ 0.0025 - < 0.01%
CAS: 26530-20-1 EINECS: 247-761-7 Index number: 613-112-00- REACH: 01-2120768921-45	1, H314; Eye Dam. 1, H318; \spadesuit Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); \spadesuit Skin Sens. 1A, H317, EUH071 ATE: LD ₅₀ oral: 125 mg/kg LD ₅₀ dermal: 311 mg/kg Specific concentration limit: Skin Sens.1A; H317: C \geq 0.0015 %	≥ 0.00025 - < 0.0015%
CAS: 64359-81-5 EINECS: 264-843-8 Index number: 613-335-00- REACH: ²	4,5-dichloro-2-octyl-2H-isothiazol-3-one Acute Tox. 2, H330; Skin Corr. 1C, H314; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 ATE: LD₅o oral: 567 mg/kg Specific concentration limits: Skin Irrit. 2;H315: C ≥ 0.025 % Eye Irrit. 2; H319: C ≥ 0.025 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥ 0.00025 - < 0.0015%
CAS: 2682-20-4 EINECS: 220-239-6 REACH: 01-2120764690-50	2-Methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 1, H410 (M=1); Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1;H317: C ≥ 0.0015 %	< 0.0015%
Other components (>20%):	·	
CAS: 1317-65-3 Limesto EINECS: 215-279-6 Consist REACH: 1 Calcium (0 - 10	ne (Calcium carbonate) ng of: 471-34-1 Calcium carbonate (> 90%) /Magesium carbonate (0 - 10%); 14808-60-7 %); 37244-96-5 Feldspar (0 - 5%); 12001 um aluminum silicate (Muscovite) (0 - 5%)	Quartz (SiO₂)
CAS: 7732-18-5 EINECS: 231-791-2 REACH: 1		25 - 50%
		(Contd. on page 4)



Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8) Revision: 26.05.2023

BIOFARBA 008

(Contd. of page 3)

Additional information:

For the wording of the listed hazard phrases refer to section 16.

Note 10 (EU 2020/217): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 μ m.

¹ Not subject to registration in accordance with EC 1907/2006 Annex V (point 7) or Article 2.

SECTION 4: First aid measures

Description of first aid measures



First aid

General information:

For first responder no special personal protective equipment is required. First responder should avoid contact with the product.

After inhalation:

Take affected persons into fresh air and keep quiet. Seek medical treatment in case of complaints. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Immediately remove all soiled and contaminated clothing. Wash contaminated clothes before reuse. Clean contamionated shoes before reuse. If skin irritation continues, consult a doctor.

After eye contact:

Do not rub eyes because additional damage to eyes can be caused by mechanical stress. If necessary, remove contact lenses and flush the eye immediately while holding eyelids open to water for at least 20 minutes. If possible, isotonic eyewash solution (e. g. 0,9% NaCl). Always consult an occupational physician or ophthalmologist.

After swallowing:

Do not induce vomiting. If conscious rinse mouth with water and drink plenty of water. Consult a physician or poison control center.

Most important symptoms and effects, both acute and delayed

Symptoms and effects are described in section 2 and 11.

Hazards:

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

If a physician is to be consulted, as per possibillity he should be presented this safety data sheet.

SECTION 5: Firefighting measures

Extinguishing media

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

Suitable extinguishing agents:

The mixture is flammable neither in the delivery condition not in mixed conditions. Extinguisher and fire fighting are therefore adjusted to the surrounding fire.

(Contd. on page 5)



Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8) Revision: 26.05.2023

BIOFARBA 008

(Contd. of page 4)

Special hazards arising from the substance or mixture

This product is neither explosive nor flammable, and non-oxidizing with other materials. Particular danger of slipping on leaked/spilled product.

Advice for firefighters

No special measures required. Collect contaminated fire fighting water separately. It must not enter the sewage system. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

If appropriate, reference must be made to exposure controls and personal protection (see section 8).

Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace. Avoid contact with the eyes and skin. Wear protective clothing. Washing facilities / Water for cleaning yes and skin should be available. Persons, who tend to skin diseases or other hypersensitivity reactions of the skin, should not handle the product. Do not eat, drink, smoke or sniff while working.

Information about fire - and explosion protection:

No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Keep out of reach of children. Store in cool, dry place in tightly closed receptacles.

Information about storage in one common storage facility:

Keep away from foodstuffs, beverages and feed.

Further information about storage conditions:

Protect from frost. Protect from heat and direct sunlight.

Miniumum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

Storage class: 12

Specific end use(s)

No further relevant information available.

GB



Printing date 26.05.2023 Version number: RO/ 9 (replaces version 8) Revision: 26.05.2023

BIOFARBA 008

(Contd. of page 5)

Control p	arameters			
		ues that require	e monitoring at the workplace:	
			les ≤ 10µm, Note 10)	
WEL (Gre		term value: 10* 4 inhalable **respi		
			silicate (Muscovite)	
`	*total	-term value: 10* (inhalable **respi		
	ropane-1,2-diol			
WEL (Gre			* 10** mg/m³, 150* ppm iculates **particulates	
DNELs				
		• •	les ≤ 10μm, Note 10)	
Oral	Long term expo		700 mg/kg bw/d (Consumer)	
		g term exposure	10 mg/m³ (Employee)	
	ropane-1,2-diol			
Inhalative	Systemic - Long	g term exposure	,	
	_		10 mg/m³ (Employee)	
	Systemic - Shor	rt term exposure	,	
			168 mg/m³ (Employee)	
	1,2-Benzisothi	• •		
Dermal	Systemic - Long	g term exposure	,	
			0.966 mg/kg bw/d (Employee)	
Inhalative	Systemic - Long	g term exposure	1.2 mg/m³ (Consumer)	
			6.81 mg/m³ (Employee)	
	2-Methyl-2H-is			
Oral	Long term expo		0.027 mg/kg bw/d (Consumer)	
	Short term expo		0.053 mg/kg bw/d (Consumer)	
Inhalative	Local - Long ter	m exposure	0.021 mg/m³ (Consumer)	
			0.021 mg/m³ (Employee)	
	Local - Short te	rm exposure	0.34 mg/m³ (Consumer)	
			0.34 mg/m³ (Employee)	
PNECs				
		•	les ≤ 10µm, Note 10)	
Freshwate	r	0.127 mg/l		
Marine wa	ter	1 mg/l		
Soil		> 100 mg/kg		
Sediments	(Freshwater)	> 1,000 mg/kg		
Sediments	(Marine water)	100 mg/kg		
Sewage pl		100 mg/l		
	ropane-1,2-diol			
Freshwate	r	260 mg/l (not sp	pecified)	
Marine wa	ter	26 mg/l (not spe	•	
Soil		50 mg/kg (not s	pecified)	
Sediments (Freshwater)		572 mg/kg (not		



Printing date 26.05.2023 Version number: RO/ 9 (replaces version 8) Revision: 26.05.2023

BIOFARBA 008

	(Contd. of page	
Sediments (Marine water)	57.2 mg/kg (not specified)	
Sewage plant	20,000 mg/l (not specified)	
2634-33-5 1,2-Benzisothiazol-3(2H)-one		
Freshwater	0.00403 mg/l (not specified)	
Marine water	0.000403 mg/l (not specified)	
Soil	3 mg/kg (not specified)	
Sediments (Freshwater)	0.0499 mg/kg (not specified)	
Sediments (Marine water)	0.000499 mg/kg (not specified)	
Sewage plant	1.03 mg/l (not specified)	
26530-20-1 2-Octyl-2H-isothiazol-3-one		
Freshwater	0.0022 mg/l (not specified)	
Marine water	0.00022 mg/l (not specified)	
Soil	0.0082 mg/kg (not specified)	
Sewage plant	0.0475 mg/l (not specified)	
2682-20-4 2-Methyl-2H-is	othiazol-3-one	
Freshwater	0.00339 mg/l (not specified)	
Soil	0.047 mg/kg (not specified)	
Sediments (Marine water)	0.00339 mg/kg (not specified)	
Sewage plant	0.23 mg/l (not specified)	

Ingredients with biological limit values:

Void

Additional Occupational Exposure Limit Values for possible hazards during processing:	
14808-60-7 Silicon dioxide (fine dust)	
BOELV (EU) Long-term value: 0.1* mg/m³ *respirable fraction	

Additional information:

The lists valid during the making were used as basis.

Exposure controls

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Remove contaminated clothing immediately and thoroughly clean it before using it again. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection. Ensure that washing facilities are available at the work place.

Respiratory protection:



Use suitable respiratory protective device only when aerosol or mist is formed (FFP2 according to EN 149)

Hand protection:



Hand protection: Chemical resistant protective gloves according EN ISO 374

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material (Contd. on page 8)



Printing date 26.05.2023 Version number: RO/ 9 (replaces version 8) Revision: 26.05.2023

BIOFARBA 008

(Contd. of page 7)

on consideration of the penetration times, rates of diffusion and the degradation. Check protective gloves prior to each use for their proper condition. Preventive skin protection by use of skin-protecting agents is recommended. To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the permanent contact gloves made of the following materials are suitable:

Polychloroprene (material thickness ≥ 0.5 mm; breakthrough time ≥ 480 min.) Nitrile rubber (material thickness ≥ 0.35 mm; breakthrough time ≥ 480 min.) Butyl rubber (material thickness ≥ 0.5 mm; breakthrough time ≥ 480 min.) Fluororubber (material thickness ≥ 0.4 mm; breakthrough time ≥ 480 min.)

Synthetic rubber gloves

PVC gloves

Neoprene protective gloves with a material thickness of $\geq 0.5 \ \text{mm}$ are recommended.

Neoprene gloves

Not suitable are gloves made of the following materials:

Non-liquid-tight gloves made of fabric, leather or similar materials.

Eye/face protection:



In case of splash risk use tightly fitting safety goggles according to EN 166.

Body protection:



Protective work clothing

Risk management measures:

An operator training/guidance in the correct use of personal protective equipment is necessary to ensure the required level of effectiveness.

Information about design of technical facilities

No further data; see item 7.

Environmental exposure controls

Avoid release in the environment. Use the surplus or dispose it of properly.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

General Information

Physical state Fluid

Appearance:

Form: Fluid

Colour: Different according to colouring

Odour: Mild

(Contd. on page 9)



Printing date 26.05.2023 Version number: RO/ 9 (replaces version 8) Revision: 26.05.2023

BIOFARBA 008

(Contd. of page 8)

Odour threshold: Not safety relevant

pH at 20 °C (68 °F) 8 - 10

Change in condition

Melting point/freezing point: $\sim 0 \, ^{\circ}\text{C} \, (\sim 32 \, ^{\circ}\text{F}) \, (ISO \, 3016)$

Boiling point or initial boiling point and

boiling range 100 °C (212 °F)

Flammability Product is not flammable.

Flash point: Not applicable

Auto-ignition temperature: > 400 °C (> 752 °F) (DIN 51794)

Decomposition temperature: > 825°C to CaO and CO₂

Oxidising properties: None

Explosive properties: Product does not present an explosion hazard.

Lower and upper explosion limit

Lower: Not determined Upper: Not determined

Ignition temperature: Product is not selfigniting. **Vapour pressure at 20 °C (68 °F):** 23 hPa (17.3 mm Hg)

Density and/or relative density

Density at 20 °C (68 °F): 1.4 - 1.6 g/cm³ (11.68 - 13.35 lbs/gal)

Particle size Viscosity:

Dynamic at 20 °C (68 °F): > 1,000 mPas (DIN 53019)

Solubility

Water: Fully miscible Solids content: 60 - 64 %

Solvent content:

Organic solvents: < 1.1 %

VOC without water (EC): 28.13 - < 37.51 g/l **VOC** with water (EC): 14.06 - < 16.06 g/l

VOC with water (EC): < 1.004 %

Other information

Information with regard to physical hazard

classes Explosives

Void Flammable gases Void **Aerosols** Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void **Pyrophoric liquids** Void **Pyrophoric solids** Void Self-heating substances and mixtures Void Substances and mixtures, which emit

Substances and mixtures, which emit
flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Void
Desensitised explosives

GB



Revision: 26.05.2023

Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8)

BIOFARBA 008

(Contd. of page 9)

SECTION 10: Stability and reactivity

Reactivity

No dangerous reactions known.

Chemical stability:

The product is stable as long as it is stored properly and dry.

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions

No dangerous reactions known.

Conditions to avoid

No further relevant information available.

Incompatible materials

No further relevant information available.

Hazardous decomposition products

No dangerous decomposition products known.

Miniumum storage life:

Minimum storage life (+5°C up to 25°C): See indication on package.

Additional information:

No further relevant information available.

SECTION 11: Toxicological information

Information on hazard classes as defined in Regulation (EC) No 1272/2008

The product was not investigated. The statement is derivated from the properties of the single components.

Acute toxicity:

Based on available data, the classification criteria are not met.

Oral 13463-67 Oral	LD ₅₀	6,450 mg/kg (Rat) (RTECS Data) ide (<1% particles ≤ 10μm, Note 10) > 5,000 mg/kg (Rat) (OECD 425) (Mouse) (ECHA Registration dossier)
	LD ₅₀	> 5,000 mg/kg (Rat) (OECD 425)
Oral	1	
	Carcinogenicity	(Mouse) (ECHA Registration dossier)
		no effects observed
Dermal	LD ₅₀	> 5,000 mg/kg (Rabbit)
57-55-6 P	Propane-1,2-diol	
Oral	LD ₅₀	> 2,000 mg/kg (Rat) (OECD 401 Acute Oral Toxicity)
Dermal	LD ₅₀	20,800 mg/kg (Rabbit) (OECD 402 Acute Dermal Toxicity)
2634-33-	5 1,2-Benzisothia	azol-3(2H)-one
Oral	LD ₅₀	1,150 mg/kg (Mouse)
		597 mg/kg (Rat)
Dermal	LD ₅₀	> 2,000 mg/kg (Rat)
886-50-0	2-tert-Butylamin	o-4-ethylamino-6-methylthio-s-triazine (Terbutryn)
Oral	LD ₅₀	500 mg/kg (Rat) (OECD 423) S 1219

(Contd. on page 11)



Printing date 26.05.2023 Version number: RO/ 9 (replaces version 8) Revision: 26.05.2023

BIOFARBA 008

		(Co	ontd. of page 10	
Dermal	LD ₅₀	> 2,000 mg/kg (Rat) (OECD 402) S 1220		
Inhalative	LC ₅₀ (4h)	5.21 mg/l (Rat) (OECD 403) S 1221, dust		
26530-20-	26530-20-1 2-Octyl-2H-isothiazol-3-one			
Oral	LD ₅₀	125 mg/kg (ATE)		
		125 mg/kg (Rat) (OECD 401)		
Dermal	LD ₅₀	311 mg/kg (ATE)		
		311 mg/kg (Rat) (OECD 402)		
Inhalative	LC ₅₀ (4h)	0.5 mg/l (ATE)		
64359-81-	5 4,5-dichloro-2	2-octyl-2H-isothiazol-3-one		
Oral	LD ₅₀	567 mg/kg (ATE)		
Inhalative	LC ₅₀ (4h)	0.05 mg/l (ATE)		
	LC ₅₀ (4h)	0.055 - 0.53 mg/l (Rat)		
2682-20-4	2-Methyl-2H-is	othiazol-3-one		
Oral	LD ₅₀	232 - 249 mg/kg (Rat) (OECD 401)		
Dermal	LD ₅₀	242 mg/kg (Rat) (OECD 402)		
Inhalative	LC ₅₀ (4h)	0.05 mg/l (ATE)		
	LC₅₀ (4h)	0.11 mg/l (Rat) (OECD 403)		

13463-67-7 Tita	nium dioxide (<1% particles ≤ 10µm, N	lote 10)
Oral	OECD 414 (Prenatal Developmental	
	Toxicity)	no effects observed
Irritation of skin	OECD 404 (skin)	(Rabbit)
		not corrosive
Irritation of eyes	OECD 405 (eye)	(Rabbit)
		not irritant
Sensitisation	OECD 429 (LLNA)	(Mouse)
		not sensitizing
	OECD 421 (Reproduction screening	
	test)	no effects observed
886-50-0 2-tert-l	Butylamino-4-ethylamino-6-methylthio	<u> </u>
Oral	OECD 414 (Prenatal Developmental	
	Toxicity)	S 1358
	OECD 471 (In vitro - Mutation, Ames- Test)	(Salmonella typhimurium) (OECD 471) S 1231
	OECD 473 (In vitro - Mutation)	(Chinese hamster, oocyte) (OECD 473 S 1232
	OECD 476 (In vitro - Mutation)	(Chinese hamster, oocyte) (OECD 476 S 1233
lumitation of alsim	OECD 404 (skin)	(Rabbit) (OECD 404)
imiation of Skin		not irritant - S 1222
	OECD 405 (eye)	(Rabbit) (OECD 405) not irritant - S 1419



Revision: 26.05.2023

Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8)

BIOFARBA 008

		(Contd. of page 1
26530-20-1 2-O	ctyl-2H-isothiazol-3-one	
Oral	OECD 471 (In vitro - Mutation, Ames- Test)	(Salmonella typhimurium) Negative
Irritation of skin	OECD 404 (skin)	(Rabbit) Corrosive Category 1B
Irritation of eyes	OECD 405 (eye)	(Rabbit) Irreversible effects Category 1
Sensitisation	OECD 406 (sensitization)	(Guinea pig) Sensitizing Category 1
2682-20-4 2-Met	thyl-2H-isothiazol-3-one	
Oral	OECD 408 (Repeated dose oral toxicity 90d)	19 mg/kg bw/day (Rat)
Irritation of skin	OECD 404 (skin)	(Rabbit) corrosive
Sensitisation	OECD 406 (sensitization)	(Guinea pig) sensitizing

On the skin:

Based on available data, the classification criteria are not met.

On the eye:

Based on available data, the classification criteria are not met.

Sensitization:

Sensitising effect by skin contact is possible by prolonged exposure.

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure (STOT SE):

Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure (STOT RE):

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Practical experience

No further relevant information available.

General comments

No further relevant information available.

Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

Toxicity

The product was not investigated. The statement is derivated from the properties of the single components.

(Contd. on page 13)



Printing date 26.05.2023 Version number: RO/ 9 (replaces version 8) Revision: 26.05.2023

BIOFARBA 008

Aquatic toxicity:	(Contd. of pag
1317-65-3 Limestone (Calciu	ım carbonate)
LC ₅₀ (96h)	> 100 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)
LC ₅₀ (48h)	> 100 mg/l (Water flea - daphnia magma) (OECD 202)
EC ₅₀ (1011)	> 14 mg/l (Algae - desmodesmus subspicatus) (OECD 201)
250	> 1,000 mg/l (Activated sewage sludge) (OECD 209)
13463-67-7 Titanium dioxide	(<1% particles ≤ 10μm, Note 10)
LC ₅₀ (48h)	5.5 mg/l (Water flea - daphnia magma)
LC ₅₀ (96h Marine water)	> 10,000 mg/l (Fish)
LC ₅₀ (96h Freshwater) (static)	
EC ₅₀ (48h)	> 1,000 mg/l (Water flea - daphnia magma) (ASTM Standard E7
EC ₅₀ (72h)	5.83 mg/l (Algae - pseudokirchneriella subcapitata)
EC ₅₀ (3h)	> 1,000 mg/l (Activated sludge organisms) (OECD 209)
EC ₅₀ (7d)	> 100 mg/l (Lemna minor) (OECD 221)
NOEC (48h)	1 mg/l (Water flea - daphnia magma)
NOEC (21d)	> 10 mg/kg (Water flea - daphnia magma) (OECD 202)
NOEC (28d) (static)	> 100 mg/l (Chironomus riparius) (OECD 219)
	Soil
NOEC (32d)	> 1 mg/l (Scenedesmus quadricauda)
NOEC (8d)	> 1,000 mg/l (Zebrafish - danio rerio) (OECD 212)
57-55-6 Propane-1,2-diol	
LC ₅₀ (96h)	18,800 mg/l (Americamysis bahia)
	40,613 mg/l (Rainbow trout - oncorhynchus mykis)
LC ₅₀ (48h)	18,340 mg/l (Water flea - ceriodaphnia dubia)
LC ₅₀	6,983 mg/l (Corophium volutator)
	317 mg/l (Rabbit) (OECD 403 Acute Inhalation Toxicity)
EC ₅₀ (96h)	19,000 mg/l (Algae - pseudokirchneriella subcapitata) (OECD : Freshwater Grow Inhibition Test)
	19,100 mg/l (Skeletonema costatum) (OECD 201 Freshwater G Inhibition Test)
NOEC (18h)	> 20,000 mg/l (Algae - pseudokirchneriella subcapitata)
NOEC (7d)	13,020 mg/l (Water flea - ceriodaphnia dubia)
2634-33-5 1,2-Benzisothiazo	I-3(2H)-one
LC ₅₀ (96h)	1.6 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)
EC ₅₀ (48h)	3.27 mg/l (Water flea - daphnia magma)
	1.5 mg/l (Water flea - daphnia)
EC ₅₀ (72h)	0.11 mg/l (Algae - selenastrum capricornutum) (OECD 201)
	2 mg/l (Algae scenedesmus subcapitatus)
EC ₅₀ (16h)	0.4 mg/l (Pseudomonas putida)
EC ₁₀ (72h)	0.04 mg/l (Algae - selenastrum capricornutum) (OECD 201)
NOEC (21d)	1.2 mg/l (Water flea - daphnia magma) (OECD 202)
NOEC (28d)	0.21 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 215)
	-ethylamino-6-methylthio-s-triazine (Terbutryn)
LC ₅₀ (96h)	1.9 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203) S 1242
EC ₅₀ (48h)	6.4 mg/l (Water flea - daphnia)



Version number: RO/ 9 (replaces version 8) Printing date 26.05.2023 Revision: 26.05.2023

BIOFARBA 008

EC ₅₀ (72h)	(Contd. of pa 0.0067 mg/l (Algae - desmodesmus subspicatus) (OECD 201)
-O ₅₀ (1∠II)	S 1244
C ₅₀ (72h)	0.0055 mg/l (Algae - selenastrum capricornutum) (OECD 201)
NOEC (72h)	0.0005 mg/l (Algae - desmodesmus subspicatus) (OECD 201) S 1244
NOEC (21d)	0.05 mg/l (Water flea - daphnia) (OECD 211) S 1240
NOEC (28d)	0.073 mg/l (Fat head minnow - pimephales promelas) (OECD 27 S 1241
26530-20-1 2-Octyl-2H-iso	thiazol-3-one
LC ₅₀ (96h)	0.03 mg/l (Rainbow trout - oncorhynchus mykis)
LC₅₀ (96h Freshwater)	0.122 mg/l (Fish - pisces)
EC ₁₀	0.068 mg/l (Algae)
	0.022 mg/l (Fish - pisces)
	0.035 mg/l (Invertebrate)
EC ₅₀	30.4 mg/l (Activated sewage sludge)
EC₅₀ (48h)	0.32 mg/l (Water flea - daphnia magma)
•	0.42 mg/l (Water flea - daphnia) (OECD 202)
EC₅₀ (72h)	0.084 mg/l (Algae scenedesmus subcapitatus) (OECD 201) S 63
EC₅₀ (96h)	0.047 mg/l (Rainbow trout - oncorhynchus mykis) (OECD 203)
EC ₅₀ /LC ₅₀	0.15 mg/l (Algae)
	0.181 mg/l (Invertebrate)
C ₅₀ (72h)	0.084 mg/l (Algae scenedesmus subcapitatus) (OECD 201)
64359-81-5 4,5-dichloro-2	octyl-2H-isothiazol-3-one
_C ₅₀ (96h)	0.014 mg/l (Perch - lepomis macrochirus) (OECD 203)
	0.0027 mg/l (Rainbow trout - oncorhynchus mykis)
EC ₅₀	5.7 mg/l (Activated sludge organisms)
ErC₅₀ (72h)	0.077 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201
EC ₅₀ (48h)	0.0057 mg/l (Water flea - daphnia magma)
EC ₅₀ (72h)	0.048 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201
NOEC (96h)	0.00056 mg/l (Rainbow trout - oncorhynchus mykis)
2682-20-4 2-Methyl-2H-isc	
_C₅₀ (96h Marine water)	2.98 mg/l (Water flea - daphnia magma)
_C₅₀ (96h Freshwater)	0.934 mg/l (Water flea - daphnia magma)
_C ₅₀	4.77 mg/l (Fish) (OECD 203)
EC₁0	0.044 mg/l (Water flea - daphnia magma) (OECD 211)
	4.93 mg/l (Fish)
EC₅o	41 mg/l (Activated sewage sludge) (OECD 209)
	0.103 mg/l (Algae - pseudokirchneriella subcapitata) (OECD 201
EC₅₀ (16h)	2.3 mg/l (Pseudomonas putida)

Persistence and degradability
A part of the components is biodegradable.

2653	0-20-1 2-Octyl-2H-isothiazol-3-one
Oral	OECD 309 Simulation Biodegradation - Surface Water 0.6 - 1.4 d (not specified) S 635
	(Contd. on page 15



Revision: 26.05.2023

Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8)

BIOFARBA 008

			(Contd. of page 1
Degree of elimi	ination:		
57-55-6 Propan	e-1,2-diol		
Biodegradation			
	105 d		
	81.7 % (Water) 28 d		
2624 22 5 4 2 5	Z8 0 Benzisothiazol-3(2H)-one		
•	> 70 % (Activated sewage	sludge) (OECD 303 A)	
Diodegradation	> 90 % (not specified) (OE	,	
886-50-0 2-tort-	, , , , ,	o-6-methylthio-s-triazine (Terbutryn)	
	< 70 % (Activated sewage	` ` ` `	
Biodogradation	S 1237	cladge) (0202 0007.)	
	0 % (Activated sludge orga	anisms) (OECD 301 F)	
	S 1238		
Bioaccumulativ	ve potential		
2634-33-5 1,2-E	Benzisothiazol-3(2H)-one		
Log Kow		0.7 (not specified) (OECD 117)	
886-50-0 2-tert-	Butylamino-4-ethylamino	-6-methylthio-s-triazine (Terbutryn)	
Log Kow		3.19 (not specified) (OECD 117)	
00500 00 4 0 0	atal Oll is athiomal O and	S 1211	
	ctyl-2H-isothiazol-3-one Kow (Shake Flask Method)	2.02 (n. Ostanol/Mater)	
		2.92 (II-Octanol/Water)	
	on factor (BCF)		
•	Benzisothiazol-3(2H)-one	'C 1) (OFOR 005)	
	n factor (BCF) 6.95 (not sp	, ,	
		o-6-methylthio-s-triazine (Terbutryn)	
Bioconcentration	n factor (BCF) 103 (Calcula EPWIN	ated)	

Mobility in soil

No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Endocrine disrupting propertiesThe product does not contain substances with endocrine disrupting properties.

Other adverse effects

No further relevant information available.

Literature

No further relevant information available.

Ecotoxical effects:

No further relevant information available.

Remark:

Harmful to fish

Behaviour in sewage processing plants:	
2634-33-5 1,2-Benzisothiazol-3(2H)-one	
EC ₂₀ (0,5h)	3.3 mg/l (Activated sludge organisms) (OECD 209)
EC ₂₀ (3h)	3.3 mg/l (Activated sludge organisms) (OECD 209)
	(Contd. on page 16)



Revision: 26.05.2023

Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8)

BIOFARBA 008

	(Contd. of page 15)
EC ₅₀ (3h)	13 mg/l (Activated sludge organisms) (OECD 209)
OECD 302 B Zahn Wellens Test	90 % (Activated sludge organisms) (OECD 302)
OECD 303 A Activated Sludge Units	% (Rat)
	> 70 % (Activated sludge organisms) (OECD 303 A)
886-50-0 2-tert-Butylamino-4-ethyla	amino-6-methylthio-s-triazine (Terbutryn)
EC ₂₀ (3h)	> 100 mg/l (Activated sludge organisms) (OECD 209)
26530-20-1 2-Octyl-2H-isothiazol-3-one	
EC ₂₀ (0,5h)	10.4 mg/l (Activated sewage sludge) (TTC-Test 8901 Macherey Nagel)
EC ₂₀ (3h)	7.3 mg/l (Activated sewage sludge) (OECD 209)
OECD 303 A Activated Sludge Units	> 83 % (Activated sewage sludge) S 313
2682-20-4 2-Methyl-2H-isothiazol-3-one	
EC ₂₀ (3h)	2.8 mg/l (Activated sludge organisms) (DIN 38412-3 TTC-Test)

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

Waste treatment methods

Recommendation:





Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Dispose of contents/container in accordance with local/regional/national/international regulations.

08 01 12 for residues of the unprocessed product 15 01 02 for the completely emptied packaging

Uncleaned packaging

Recommendation:

Disposal must be made according to official regulations.

Recycle only completely emptied packaging.

Recommended cleansing agents:

Water, if necessary together with cleansing agents.

SECTION 14	Transnor	tinforma	tion
SECTION 14	Παπορυπ	. IIII OI III a	

UN number or ID number		
ADR, ADN, IMDG, IATA	Void	
UN proper shipping name		
ADR, ADN, IMDG, IATA	Void	

(Contd. on page 17)



Revision: 26.05.2023

Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8)

BIOFARBA 008

		(Contd. of page 1
Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
Packing group		
ADR, IMDG, IATA	Void	
Environmental hazards		
Marine pollutant:	No	
Special precautions for user	Not applicable	
Maritime transport in bulk according	g to IMO	
instruments	Not applicable	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms Void

Signal word Void

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container in keeping with local and national regulations.

Directive (EU) 2012/18

Named dangerous substances - ANNEX I:

None of the ingredients is listed.

Biozide ingredients (98/8/EG):

Data based on recipe and information on the raw materials from the supply chain.

Tetramethylolacetylene diurea	< 0.03%
1,2-Benzisothiazol-3(2H)-one	< 0.01%
2-tert-Butylamino-4-ethylamino-6-methylthio-s-triazine (Terbutryn)	≥ 0.0025 - < 0.01%
2-Bromo-2-nitropropane-1,3-diol	≥ 0.0025 - < 0.005%
3-lodo-2-propynylbutylcarbamate	< 0.005%
2-Octyl-2H-isothiazol-3-one	≥ 0.00025 - < 0.0015%
4,5-dichloro-2-octyl-2H-isothiazol-3-one	≥ 0.00025 - < 0.0015%
2-Methyl-2H-isothiazol-3-one	< 0.0015%

Classification according 2004/42/EG:

IIA(a) 30 - This product contains < 30 g/I VOC (see chapter 9)

IIA(c) 40 - this product contains < 40 g/I VOC (see chapter 9)

(Contd. on page 18)



Printing date 26.05.2023 Version number: RO/ 9 (replaces version 8) Revision: 26.05.2023

BIOFARBA 008

(Contd. of page 17)

Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Reasons for changes:

* Data compared to the previous version altered.

Relevant phrases:

H301	l oxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Advice for instructions:

Additional trainings, which go beyond the prescribed training in activities involving hazardous substances are not required.

Literature and the data sources:

Department issuing MSDS:

Product safety department (+43/(0)5522-41646-0 / klaus.ritter@fixit-gruppe.com)

Contact:

Dr. Klaus Ritter

Date of previous version: 23.12.2022 Version number of previous version: 8

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

MAK: Maximale Arbeitsplatz-Konzentration (maximum concentration of a chemical substance in the workplace, Austria/Germany)

PBT: persistent, bioaccumulative and toxic properties

vPvB: very persistent, bioaccumulatice properties

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

(Contd. on page 19)



Revision: 26.05.2023

Printing date 26.05.2023

Version number: RO/ 9 (replaces version 8)

(Contd. of page 18)

BIOFARBA 008

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Further information:

The information in this safety data sheet describe the safety requirements of our product and is based on our current state of our knowledge. They provide no assurance of product quality. Existing laws, ordinances and regulations, including those that are not mentioned in this data sheet must be observed by the recipient of our products in their own responsibility.

GB